

NANHAI 9 ("NH9")



For Additional Information Please Contact: COSL DRILLING

Marketing Department

P. O. Box 232, Beijing 101149, China, P.R.C

Phone: +86 010 84522511 Fax: +86 010 84522867

sh_cosldrillingmarket@cosl.com.cn

www.cosl.com.cn

General Description	
·	
Design/Generation	GVA-4500
Constructing Shipyard	DAEWOO SHIPBUILDING OKPO,KOREA
Year Enter Service/Significant Upgrades	1988
Classification	DNV&CCS
Flag	China
Displacement	35,560tons
Variable Deck	3,798tons
Operating Water Depth	5,300ft
Maximum Drilling Depth	25,000ft
Accomodation	130
Drilling Equipment	
Top Drive	Varco-TDS-4H,1,100HP, 10,000psi
Draw works	EMSCO/C-3 TYPE II, 2,250hp continuous input power,1-3/4in drilling line
Derrick	Maritime Hydraulic Dynamic Derrick
Mud Pumps	Continental Emsco FB-1600, working pressure: 5,000 psi
Storage Capacities	
Fuel Oil	10,606bbls
Liquid Mud	3860bbls
Base Oil	817bbls
Brine	3,333bbls
Drill Water	10,812bbls
Portable Water	2,968bbls
BOP & Subsea Equipment	
BOP Rams	2 x Hydril 18 3/4in 15,000psi double rams;
-	-



BOP Annular	Shaffer 18 3/4in 10,000 psi annular	
Moon Pool	96.5ft x 60ft	
Tensioner	Western/ riser tensioner	
Other Information		
Cranes	75t x 2	
Heli-deck	SikorskyS61N11/BOEINGCHINOOK 234 Helicopter	
Station Keeping	Mooring system	

NANHAI 9 ("NH9")





