

GULF DRILLER 1 (“GD1”)


For Additional Information Please Contact:
COSL DRILLING
Marketing Department
P. O. Box 232, Beijing 101149, China, P.R.C
Phone: +86 010 84522511
Fax: +86 010 84522867
sh_cosldrillingmarket@cosl.com.cn
www.cosl.com.cn

General Description

| | |
|---|----------------------------------|
| Design/Generation | Friede & Goldman, Super M2 |
| Constructing Shipyard | Yantai CIMC Raffles Offshore LTD |
| Year Enter Service/Significant Upgrades | 2013 |
| Classification | ABS |
| Flag | Liberia |
| Displacement | 11,410tons |
| Variable Deck | 3,080tons |
| Operating Water Depth | 300ft |
| Maximum Drilling Depth | 30,000ft |
| Accomodation | 110 |

Drilling Equipment

| | |
|------------|--------------------------------------|
| Top Drive | Canrig, 1,150HP, 7,500psi |
| Draw works | TSC/D3000 with 2x1,500HPAC |
| Derrick | TSC bolted Single Static Bottle Neck |
| Cantilever | 50ftx 15ft |
| Mud Pumps | TSC-WF2000 x 3, 2000HPeach, 7,500psi |

Storage Capacities

| | |
|----------------|-----------|
| Fuel Oil | 4,138bbls |
| Liquid Mud | 2,289bbls |
| Base Oil | 899bbls |
| Brine | 899bbls |
| Drill Water | 6,459bbls |
| Portable Water | 2,364bbls |

BOP & Subsea Equipment

| | |
|----------|---|
| BOP Rams | C a m e r o n / U - T Y P E x13-5/8x15,000psiWPSingleRam Cameron/U- TYPE x 13-5/8"x 15,000psiWP Dual Ram BOPs |
|----------|---|

