

NANHAI 4("NH4")

	For Additional Information Please Contact: COSL DRILLING Marketing Department P. O. Box 232, Beijing 101149, China, P.R.C Phone: +86 010 84522511 Fax: +86 010 84522867 sh_cosldrillingmarket@cosl.com.cn www.cosl.com.cn
General Description	
Design/Generation	ETA/Robin Loh R300
Constructing Shipyard	Hitachi Zosen, Osaka Works Sakai, Japan
Year Enter Service/Significant Upgrades	1980
Classification	ABS+AI
Flag	China
Displacement	8,133tons
Variable Deck	2,517tons
Operating Water Depth	300ft
Maximum Drilling Depth	20,000ft
Accommodation	114
Drilling Equipment	
Top Drive	CANRIG 1275AC-681, 1,130HP, 7,500psi
Draw works	National with 2 x 1,000HPDC
Derrick	NATIONAL OILWELL
Cantilever	65ftx 12ft
Mud Pumps	BOMC F-1600HL x 2, 1,600HPeach, 7,500psi BOMC F-1600 x 1, 1,300HP, 5,000psi
Storage Capacities	
Fuel Oil	5,419bbls
Liquid Mud	2,836bbls
Base Oil	---
Brine	---
Drill Water	5,759bbls
Portable Water	3,229bbls
BOP & Subsea Equipment	

BOP Rams	Shaffer x 13-5/8" x 15,000psiWP Single Ram , Shaffer x 13-5/8" x 15,000psiWP Dual Ram BOPs
BOP Annular	Shaffer x 13-5/8" x 5,000psiWP Annular
Diverter	---
Other Information	
Cranes	36ton x 2, 47ton x 1
Heli-deck	Sikorski S61 N Helicopter
Containment System	zero discharge

NANHAI 4 ("NH4")



