

**COSL POWER**

	For Additional Information Please Contact: COSL DRILLING Marketing Department P. O. Box 232, Beijing 101149, China, P.R.C Phone: +86 010 84522511 Fax: +86 010 84522867 <a href="mailto:sh_cosldrillingmarket@cosl.com.cn">sh_cosldrillingmarket@cosl.com.cn</a> <a href="http://www.cosl.com.cn">www.cosl.com.cn</a>
<b>General Description</b>	
Design/Generation	Baker Marine Pacific Class 375
Constructing Shipyard	PPL Shipyard Pte Ltd, Singapore
Year Enter Service/Significant Upgrades	2006
Classification	ABS
Flag	Singapore
Displacement	19,777tons
Variable Deck	3,375tons
Operating Water Depth	375ft
Maximum Drilling Depth	30,000ft
Accommodation	120
<b>Drilling Equipment</b>	
Top Drive	NationalOilwellVarco/HPS-750-E-AC-SG,1150HP,7500psi
Draw works	National Oilwell Varco / D3000UE AC,3 x1350HP
Derrick	National Oilwell Varco / Bolted H-beam
Cantilever	70ftx 15ft
Mud Pumps	NOV 14-P-220 x 3, 2 x1350HPeach,7500psi
<b>Storage Capacities</b>	
Fuel Oil	3900bbbls
Liquid Mud	4,150bbbls
Base Oil	1274bbbls
Brine	1284bbbls
Drill Water	4850bbbls
Portable Water	3600bbbls
<b>BOP &amp; Subsea Equipment</b>	
BOP Rams	Hydri I/ MPL x18¾ x 15,000psiWP, Dual Ramps x2
BOP Annular	Hydril / GX x18¾ x 10,000 psi
Diverter	Vetco Gray / KFDJ-500 Standard bore
<b>Other Information</b>	
Cranes	55.1 ton x 1; 45 ton x 1; 25 ton x 1; 9.9ton x 1
Heli-deck	Sikorski S61 N Helicopter
Containment System	zero discharge

