

COSL CONFIDENCE

	For Additional Information Please Contact: COSL DRILLING Marketing Department P. O. Box 232, Beijing 101149, China, P.R.C Phone: +86 010 84522511 Fax: +86 010 84522867 sh_cosldrillingmarket@cosl.com.cn www.cosl.com.cn
General Description	
Design/Generation	Baker Marine Pacific Class 375
Constructing Shipyard	PPL Shipyard Pte Ltd, Singapore
Year Enter Service/Significant Upgrades	2008
Classification	ABS
Flag	Singapore
Displacement	19,777tons
Variable Deck	3,375tons
Operating Water Depth	375ft
Maximum Drilling Depth	30,000ft
Accommodation	115
Drilling Equipment	
Top Drive	NationalOilwellVarco/HPS-750-E-AC-SG,1150hp,7500psi
Draw works	National Oilwell Varco / D3000UE AC,3 x1350HP
Derrick	National Oilwell Varco / Bolted H-beam
Cantilever	70ftx 15ft
Mud Pumps	NOV 14-P-220 x 3,2x1350HPeach, 7500psi
Storage Capacities	
Fuel Oil	3,654bbls
Liquid Mud	4,150bbls
Base Oil	1,698bbls
Brine	1,720bbls
Drill Water	21,920bbls
Portable Water	3,554bbls
BOP & Subsea Equipment	
BOP Rams	Shaffer/SLX18¾ x 15,000psiWP Dual Ram x2
BOP Annular	Shaffer / Wedge cover spherical model x 18¾ x 10,000 psi
Diverter	Vetco Gray / KFDJ-500 Standard bore
Other Information	
Cranes	55.1 ton x 1; 45 ton x 1; 25 ton x 1;9.9 tonx 1
Heli-deck	Sikorski S61 N Helicopter
Containment System	zero discharge

