

**NANHAI 6 (“NH6”)**


For Additional Information Please Contact:  
**COSL DRILLING**  
Marketing Department  
P. O. Box 232, Beijing 101149, China, P.R.C  
Phone: +86 010 84522511  
Fax: +86 010 84522867  
[sh\\_cosldrillingmarket@cosl.com.cn](mailto:sh_cosldrillingmarket@cosl.com.cn)  
[www.cosl.com.cn](http://www.cosl.com.cn)

**General Description**

Design/Generation	Friede & Goldman’s ENanhaianced Pacesetter
Constructing Shipyard	Götaverken, Arendal, Gothenburg, Sweden
Year Enter Service/Significant Upgrades	1982
Classification	DNV
Flag	China
Displacement	25,075 tons
Variable Deck	3,845tons
Operating Water Depth	1,371ft
Maximum Drilling Depth	22,860ft
Accomodation	100

**Drilling Equipment**

Top Drive	Varco TDS-4s
Draw works	CONTINENTAL Emsco C3 Type II, 3,000 hp continuous input power,1 1/2in drilling line
Derrick	A/S NORMAR / DYNAMIC DERRICK
Mud Pumps	1x Continental Emsco FB1600, 2x BPMMP F1600 working pressure: 5,000 psi

**Storage Capacities**

Fuel Oil	13,548bbls
Liquid Mud	2,116bbls
Base Oil	---
Brine	---
Drill Water	13,825bbls
Portable Water	3,245bbls

**BOP & Subsea Equipment**

BOP Rams	2 x Hydril 18 3/4in 15000psi double rams; CAMERON HC 18-3/4 x 15,000PSI
BOP Annular	Cameron type DL 18 3/4in 10000 psi annular
Moon Pool	18.3ft x 67.8ft
Tensioner	NL SHAFFER /twin riser tensioner
<b>Other Information</b>	
Cranes	60t x2, 50t x1
Heli-deck	Sikorsky S61N11 Helicopter
Station Keeping	Mooring system

**NANHAI 6 (“NH6”)**



