

NANHAI 8 (“NH8”)


For Additional Information Please Contact:
COSL DRILLING
Marketing Department
P. O. Box 232, Beijing 101149, China, P.R.C
Phone: +86 010 84522511
Fax: +86 010 84522867
sh_cosldrillingmarket@cosl.com.cn
www.cosl.com.cn

General Description

Design/Generation	Series9500/EnhancedPacesetterIMODU
Constructing Shipyard	Daewoo, Okpo, Korea
Year Enter Service/Significant Upgrades	1983
Classification	ABS&CCS
Flag	China
Displacement	27,664tons
Variable Deck	4,972tons
Operating Water Depth	4,600ft
Maximum Drilling Depth	25,000ft
Accommodation	120

Drilling Equipment

Top Drive	Varco-TDS-4S, 1130HP, 5000psi
Draw works	National /1625DE, 2,000hp continuous input power,1 1/2in drilling line
Derrick	Continental Ensco dynamic derrick SN-82 type -22 BDA
Mud Pumps	3xnational 12-P-160, 1600HPeach, working pressure: 5,000 psi

Storage Capacities

Fuel Oil	6,097bbls
Liquid Mud	1,825bbls
Base Oil	2,032bbls
Brine	3,585bbls
Drill Water	7,196bbls
Portable Water	2,708bbls

BOP & Subsea Equipment

BOP Rams	2 x Hydraulic 18 3/4in 15,000psi double rams;
----------	---

BOP Annular	Hydraulic GX 18 3/4in 10,000 psi annular
Moon Pool	89ft x 21ft
Tensioner	Varco / RT 80-40d / riser tensioner
Other Information	
Cranes	25t x 1, 40t x 1, 62t x 1
Heli-deck	Sikorsky S61N11 Helicopter
Station Keeping	Mooring system

NANHAI 8 (“NH8”)



