

PF-PAC-D LV

Low Viscous Polyanionic Cellulose

Revised: 2018/6/15

COSL

中海油田服务股份有限公司
China Oilfield Services Limited

DESCRIPTION

PF-PAC-D LV is decentralized polyanionic cellulose with low viscosity , its molecular weight and viscosity was lower than PAC-HV. PF-PAC-D LV is appropriate for water-based drilling fluid, especially for drilling fluid which containing solid particles, can reduce filtration loss effectively and influence rheological property lightly.

FEATURES

- Appropriate for water-based drilling fluid, especially for drilling fluid which containing solid particles, can effectively reduce filtration loss.
- Good drilling fluid compatibility, influence rheological property lightly.

APPLICATION

- Applicable temperature: $\leq 120^{\circ}\text{C}$ (BHCT)
- Suggestion dosage: 0.2%-1.5%

PACKAGE

- Packaged in 25 Kg multi—ply paper sack and within waterproof plastic film. Or based on custom's request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 24 months.

Specification

Appearance	Free flow powder
moisture, g/cm ³	≤ 10
AV mPa•s	≤ 13
API mL	≤ 9
AV (After hot aging, 120 °C&16h) mPa•s	≤ 6
API (After hot aging, 120 °C&16h) mL	≤ 11

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn

China Oilfield Services Limited

No.81, Xinggong West Street, Yanjiao, Sanhe, Hebei, China

Sungang@cosl.com.cn

+86-10-8452 3340