

DESCRIPTION

PF-GRA is a product kind of modified graphite to decrease torque, to improve the lubricity of drilling additives and filter cakes, to prevent jamming of drilling tools

FEATURES

- Excellent performance of reducing friction between drilling tools and hard formation(the same to casing pipes or other tools).
- Good compatibility with drilling fluid system, efficiently adjust the rheology and fluid loss of drilling fluid.

APPLICATION

- Applicable temperature: 180°C(BHCT)
- Suggestion dosage:2.0 ~ 3.0%

PACKAGE

- Packaged in 25 Kg multi—ply paper sack and within waterproof plastic film. Or based on custom’s request.
- It should be stored in ventilated, cool, and dry areas. Avoid being exposed to the sun and rain. Shelf life: 12 months.

Specification

Appearance	Dark grey particles
Fluorescence grade	5
Sieve residue, %	10
Reduce rate of friction, %	≥70

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn
China Oilfield Services Limited
 No.81, Xinggong West Street, Yanjiao, Sanhe,
 Hebei, China
 Sungang@cosl.com.cn
 +86-10-8452 3340