

## DESCRIPTION

PF-RT101 is a kind of vegetable grease lubricant with organic molybdenum. It is friendly to the environment. Its appearance is puce liquid. PF-RT101 can be used in freshwater drilling fluid, saltwater drilling fluid and seawater drilling fluid. It is mainly applied in the drilling process for hard formation, highly-deviated wells, extend-reach wells and horizontal wells.

## FEATURES

- Excellent performance of reducing friction between drilling tools and hard formation (the same to casing pipes or other tools); firmly adsorb on the surface of drilling tools, high extreme pressure film strength and efficiently reduce the friction even under 150oC; good dispersion and can be used in freshwater, seawater and close-saturation saltwater based drilling fluid; excellent performance in the drilling process for highly-deviated wells, overtraveling wells and quartz sand formation.

## APPLICATION

- It can be directly added into the circulation system of drilling fluid or stirred uniformly in the mud sump
- Suggestion dosage: 0.5 ~ 2.0%

## PACKAGE

- 200kg/galvanized iron drum or based on customers' request.
- It should be stored in ventilated, cool, and dry areas. Avoid being exposed to the sun and rain. Shelf life:12 months.

## Specification

Appearance	Puce liquid
Density, g/cm3	0.87 ~ 0.95
Flash point, °C	≥80
Reduce rate of friction (6% freshwater bentonite mud), %	≥80
Reduce rate of friction (6% seawater bentonite mud), %	≥70
Extreme pressure film strength, kg	≥80
Foaming rate, %	<10
Floccus	Nil

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

[www.cosl.com.cn](http://www.cosl.com.cn)

**China Oilfield Services Limited**

No.81, Xinggong West Street, Yanjiao, Sanhe, Hebei, China

Sungang@cosl.com.cn

+86-10-8452 3340