

DESCRIPTION

PF-LUBE is a kind of vegetable grease lubricant. Its appearance is tawny liquid. It adsorbs on the surface of the drilling-tools, in the form of oil film, to decrease torque, to improve the lubricity of drilling additives and filter cakes, to prevent jamming of drilling tools. PF-LUBE has good heat stability and can be used in freshwater drilling fluid, saltwater drilling fluid and seawater drilling fluid. It also has good compatibility with other additives.

FEATURES

- Excellent performance of reducing friction between drilling tools and hard formation (the same to casing pipes or other tools).
- Good compatibility with drilling fluid system, efficiently adjust the rheology and fluid loss of drilling fluid.

APPLICATION

- Applicable temperature: 180°C (BHCT)
- Suggestion dosage: 2.0 ~ 3.0%

PACKAGE

- 200L/galvanized iron drum or 1000L/plastic drum or based on customers' request.
- It should be stored in ventilated, cool, dry and clean shelters. No fire..

Specification

Appearance	Uniform liquid
Density(20°C), g/cm ³	0.85~ 0.95
Flash point, °C	50
Fluorescence grade	6
Reduce rate of torque (freshwater bentonite mud), %	60
Reduce rate of torque (seawater bentonite mud), %	≥50

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn

China Oilfield Services Limited

No.81, Xinggong West Street, Yanjiao, Sanhe, Hebei, China

Sungang@cosl.com.cn

+86-10-8452 3340