

DESCRIPTION

PF-AquaLube is a kind of high temperature resistant high performance water-based lubricant, Using in water base drilling fluid, reduce drilling tool wear resistance and torque, Improving the drilling fluid lubrication.

APPLICATION

- Temperature:Natural-180°C(BHCT).
- Suggestion dosage:2.0%-4.0%(BWOC).

PACKAGE

- 200Liter/plastic pail. Or based on custom’s request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 12 months.

Specification

Appearance		Yellow liquid
pH		6-8
Torque reduction rate (Brine),%	Rolling forward	≥80
	Rolling after(150°C)	≥80
Torque reduction rate (Natural seawater),%	Rolling forward	≥50
	Rolling after(150°C)	≥50

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn
China Oilfield Services Limited
 No.81, Xinggong West Street, Yanjiao, Sanhe,
 Hebei, China
Sungang@cosl.com.cn
 +86-10-8452 3340