

DF-MOSTRH

Oil based plugging agent

Revised: 2018/6/15

COSL
 中海油田服务股份有限公司
 China Oilfield Services Limited

DESCRIPTION

PF-MOSTRH Added to the oil base drilling fluids, can make high quality film formed on the surface of the mud shale borehole drilling fluid system, prevent drilling fluid filtrate into the formation, thus effective wellbore stability and the protection of oil reservoir

APPLICATION

- Temperature:Natural-150°C(BHCT).
- Suggestion dosage:1.0%-3.0%(BWOC).

PACKAGE

- 25KG/plastic pail. Or based on custom's request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 12 months.

Specification

Physical form (25° C)	Gray powder
pH(1% water solution)	7-10
Water content, %	≤10
60 Mesh Residue, %	15

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn
China Oilfield Services Limited
 No.81, Xinggong West Street, Yanjiao, Sanhe,
 Hebei, China
Sungang@cosl.com.cn
 +86-10-8452 3340