

**DF-FSGEL**

Organic bentonite

Revised: 2018/6/15

**COSL**

中海油田服务股份有限公司  
China Oilfield Services Limited

## DESCRIPTION

DF-FSGEL is an oil-based mud viscosifier, which provides a higher Yield Point needed to increase the carrying capacity and hole cleaning ability of OIL-BASED mud systems. DF-FSGEL is used to increase the viscosity in OIL-BASED mud systems. In addition to imparting excellent rheological properties it also provides temperature and emulsion stability and aids in fluid loss.

## APPLICATION

- Temperature: Natural-180°C (BHCT).
- Suggestion dosage: 1.0%-2.0% (BWOC).

## PACKAGE

- 25KG/plastic pail. Or based on custom's request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 12 months.

## Specification

Appearance	White free flowing powder
Sieve analysis, %100 mesh	≤ 5.0
Colloid ratio, %	≥ 90
Water content, %	≤ 5.0

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

[www.cosl.com.cn](http://www.cosl.com.cn)  
**China Oilfield Services Limited**  
 No.81, Xinggong West Street, Yanjiao, Sanhe,  
 Hebei, China  
[Sungang@cosl.com.cn](mailto:Sungang@cosl.com.cn)  
 +86-10-8452 3340