

**DF-FSWET**

Wetting agent

Revised: 2018/6/15



## DESCRIPTION

Wetting agent is a field strength 90%~95% active non ionic surfactant. It is used in invert emulsifier systems as a wetting agent. Wetting agent is designed to aid in oil-wetting of drill solids and weight agent. Also it is designed to increase emulsion stability. Wetting agent delivers premium performance across a broad temperature range and in a variety of mud formulations, aimed for deepwater drilling.

## APPLICATION

- Temperature:Natural-150°C(BHCT).
- Suggestion dosage:0.5%-1.5%(BWOC).

## PACKAGE

- 200Liter/plastic pail. Or based on custom's request.
- It should be stored in cool,dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 12 months.

## Specification

Physical form (25° C)	Colorless liquid
Specific Gravity (20° C)	0.95~1.05 g/cm3
Flash point, ° C	≥120
Pour Point, ° C	≤-10

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

[www.cosl.com.cn](http://www.cosl.com.cn)  
**China Oilfield Services Limited**  
 No.81, Xinggong West Street, Yanjiao, Sanhe,  
 Hebei, China  
[Sungang@cosl.com.cn](mailto:Sungang@cosl.com.cn)  
 +86-10-8452 3340