

## DESCRIPTION

DF-MOVIS is a mixture of polyfunctional acids and polyamides, it is a rheology modifier used to alter the low shear, low temperature viscosity of oil-based mud or synthetic-based mud. DF-MOVIS delivers premium performance across a broad temperature range and in a variety of mud formulations, especially for deepwater drilling.

## APPLICATION

- DF-MOVIS is a rheology modifier, designed for use in the field with mineral oil, or other hydrocarbons. It is typically used with lime, viscosifiers (organophilic clay) and fluid loss control agents, weight agent to formulate an oil-base or synthetic-base drilling fluid. While the quantity used may vary depending on specific conditions, it is typically used at 1~3.5 lb/bbl.

## PACKAGE

- 25KG/plastic pail. Or based on custom's request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 12 months.

### Specification

Physical form (25° C)	Brown viscous liquid
Specific Gravity (25° C)	0.90~0.96 g/cm <sup>3</sup>
Moisture content	1% maximum
Flash Point, Closed Cup	100°C Minimum
Pour Point	-15°C Minimum

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

[www.cosl.com.cn](http://www.cosl.com.cn)

**China Oilfield Services Limited**

No.81, Xinggong West Street, Yanjiao, Sanhe,  
Hebei, China

[Sungang@cosl.com.cn](mailto:Sungang@cosl.com.cn)

+86-10-8452 3340