

# PF-AQUASEAL

## Physical Plugging Agent

Revised: 2018/6/15



### DESCRIPTION

PF- AQUASEAL is a kind of modified-asphalt products, appearance is gray powder, exist with solids in the drilling fluid, and can block to the sand layer and crack, can effectively prevent sand permeability. Suitable for fresh water, salt water, sea water drilling fluid, good compatibility with other treatment agent.

### FEATURES

- Prominent plugging ability, reduce filtration effectively on sand layer;
- Good drilling fluid compatibility, regulate fluid filtration effectively.

### APPLICATION

- Applicable temperature: ≤180°C (BHCT)
- Suggestion dosage: 2%-3%

### PACKAGE

- Packaged in 25 Kg multi—ply paper sack and within waterproof plastic film. Or based on customers' request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 24 months.

### Specification

Appearance	Free flow powder
Moisture content, %	≤8
pH	8-10

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn  
**China Oilfield Services Limited**  
 No.81, Xinggong West Street, Yanjiao, Sanhe, Hebei, China  
 Sungang@cosl.com.cn  
 +86-10-8452 3340