

PF-EZCARB

Reservoir bridge plugging agent

Revised: 2018/6/15



DESCRIPTION

Reservoir bridge plugging agent PF-EZCARB is inorganic compound material, through the calculation of ideal packing bridging supporting software, using different mesh material to compound selected. PF - EZCARB has effective plugging ability for different strata.

APPLICATION

- Applicable temperature: ≤150°C(BHCT)
- Suggestion dosage: 5%-8%

PACKAGE

- Ensure PF-EZCARB’s bags have sufficient strength, which at least have two layers that Outer for triad paper-plastic composite bag and inner plastic bags. Or based on customers’ request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 24 months.

Specification

Appearance	White or light grey powder
Available Content, %	≥90.0
Moisture, %	≤3.0
Acid-insoluble substance Content, %	≤2.0
Particle distribution range	The content of particle diameter that greater than 74 microns, ≤10%

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn
China Oilfield Services Limited
 No.81, Xinggong West Street, Yanjiao, Sanhe,
 Hebei, China
 Sungang@cosl.com.cn
 +86-10-8452 3340