

PF-STRH

Drilling Pressure-resistance Agent

Revised: 2018/6/15



DESCRIPTION

PF-STRH is a kind of plugging agent with ability of improve the quality of mud cake and the loading capacity offormation by action of bridge blinding and film forming. PF-STRH made up of inert particles and delayed expansion particles. PF-STRH is suitable for all types of water-based drilling fluid, good compatibility with other admixture.

FEATURES

- The PF-STRH has good compatibility with drilling fluid system, and adjust drilling fluid rheology and filtration effectively.

APPLICATION

- Applicable temperature: ≤180°C(BHCT)
- Suggestion dosage: 1%-3%

PACKAGE

- Packaged in 25 Kg multi—ply paper sack and within waterproof plastic film. Or based on customers' request.
- It should be stored in cool, dry and ventilated areas and avoid being exposed to the sun and rain. Shelf life: 24 months.

Specification

Appearance	Free flow powder
Moisture content,%	≤5
Fineness (sieve mesh: 0.15mm, standard sieve),%	≤15
Filtration of sand bed, ml/30min	≤45

This information is supplied solely for informational purposes and COSL makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

www.cosl.com.cn
China Oilfield Services Limited
 No.81, Xinggong West Street, Yanjiao, Sanhe, Hebei, China
 Sungang@cosl.com.cn
 +86-10-8452 3340