

HAI YANG SHI YOU 922



For the additional information please contact:

MarketingDepartmentof COSL Drilling

Telephone: +86 -10 -8452 2511

Email: sh_coslmarketingmarket@cosl.com.cn

Website: www.cosl.com.cn

Office address:

No.201,Haiyou Street, Yanjiao Developing Zone,
Sanhe City, Hebei Province (Post Code: 065201)

**General Description**

Design/Generation	Friede&Goodman,/L-780 MOD II
Constructing Shipyard	Qingdao Shipyard, COOEC
Deliver Year/Upgrades	2010
Classification	ABS&CCS
Flag	China
Overall Dimensions	187.68ft L x 175ft W x 25ft D
Legs	3×308.39ft. long; Triangular
Usable leg below hull	259.183ft
Spudcan diameter	50ft
Draft at loadline (deepest)	14.583ft
Displacement at loadline	9521mt
Drilling VL	2122mt
Cantilever Envelope(Reach aft, from/to)	0/58ft
Cantilever Envelope(Transverse, port- stbd)	12/12f
Operating Water Depth	200ft
Max. Rating Drilling Depth	20,000ft
Accommodation	120 beds

Drilling Equipment

Derrick	BAOJI HJJ450/47-T7, 992080.18 lbs static hook load
Simultaneous setback + hookload capacity	567mt
Drawworks	Baoji JC-70D drawworks / 2x1973.95hp
Top Drive	Heilongjiang Jinghong /DQ70BSQ II -JH/ 1,200HP / 5,000psi
Rotary Table	Baoji ZP-375 Max. Opening 37-1/2"
Pipe Handling	Beijing JJC/ SPH-2.5/PHA-8
Mud Pumps	3 x Baoji F-1600/ 1073HP / 5,000psi
Solid Control	4* NOV /KING COBRA HYBRID shale shakers
Drilling Manifold	ChengDe KingDream 3-1/8" 10K Choke Baoji Tonghua 4" Standpipe Manifold Baoji 2" 10k cement Manifold

Power Plant

Main Power	4 x Henan Diesel /TBD620V16/ 2223.37HP Diesel Engines
Emergency Power	1 X Henan Diesel/TBD620V8 diesel engine rated 1072.8hp, 1,500 rpm

STORAGE CAPACITIES

Fuel Oil	2522 bbls
Active Liquid Mud	1874bbls
Independent Brine	497 bbls
Independent Base Oil	N/A
Drill Water	5532 bbls
Potable Water	1855 bbls
Bentonite/barite	4873.42 ft3
Cement	4873.42 ft3
Sack Storage	3,400 sacks

BOP Equipment

Diverter	N/A
BOP annular	1 x Rongsheng/ 5k 13-5/8
BOP rams	2xRongsheng/2FZ35-70 10k Double 13-5/8",
BOP handling	J.D.Neuhaus/EH30 2x30T safety working load

Cranes

Port&Stbd	2* YQHG2800-35T-18m (8T-39M; 124.67ft boom length, 35mt Max.load
Knuckle-Boom	N/A

Mooring Equipment



Anchor	Winches	4* MEP Mepsh-MWE-030-090SD,electric,
Anchor Lines		4* MEP 35W*7-3B
		1-1/2" Diameter 1968 useful length
Anchors		4* CMIC Delta Anchor, 2.8mt/each

OTHER FEATURES

Helideck	Designed for helicopter Sikorski S61 N Helicopter
Tension System	N/A

These specifications are intended for general reference purposes only. All equipment shall be operated and maintained at all times, in compliance with COSL DRILLING standard operating manuals,policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.

HAI YANG SHI YOU 922 (HYSY922)



These specifications are intended for general reference purposes only. All equipment shall be operated and maintained at all times, in compliance with COSL DRILLING standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.