

**NANHAI 1("NH1")**



For Additional Information Please Contact:  
**COSL DRILLING**  
 Marketing Department  
 P. O. Box 232, Beijing 101149, China, P.R.C  
 Phone: +86 010 84522511  
 Fax: +86 010 84522867  
[sh\\_cosldrillingmarket@cosl.com.cn](mailto:sh_cosldrillingmarket@cosl.com.cn)  
[www.cosl.com.cn](http://www.cosl.com.cn)

**General Description**

Design/Generation	ETA/Robin Loh R300
Constructing Shipyard	Robin, Singapore
Year Enter Service/Significant Upgrades	1976
Classification	CCS
Flag	China
Displacement	10,528tons
Variable Deck	2,300tons
Operating Water Depth	300ft
Maximum Drilling Depth	20,000ft
Accommodation	100

**Drilling Equipment**

Top Drive	VARCO IDS-1, 1,105HP, 5,000psi
Draw works	National 1320-UE with 2 x800HPDC
Derrick	Pyramid bolted and galvanized
Cantilever	60ftx 12ft
Mud Pumps	Baoji F-1600 x 3, 1600HPeach, 5,000psi

**Storage Capacities**

Fuel Oil	4,994bbls
Liquid Mud	2,075bbls
Base Oil	---
Brine	---
Drill Water	5,453bbls
Portable Water	2,515bbls

**BOP & Subsea Equipment**

BOP Rams	Cameron UM x 13-5/8" x 10,000psiWP Single Ram , Cameron Um x 13-5/8" x 10,000psiWP Dual Ram BOPs
BOP Annular	Shaffer x 13-5/8" x 5,000psiWP Annular
Diverter	---
<b>Other Information</b>	
Cranes	31.6ton x 2, 47ton x 1
Heli-deck	Sikorski S61 N Helicopter
Containment System	zero discharge

**NANHAI 1 ("NH1")**



