COSL BOSS

COSI Mark P. O. Phor Fax: sh_c	Additional Information Please Contact: DRILLING Leting Department Box 232, Beijing 101149, China, P.R.C Le: +86 010 84522511 +86 010 84522867 cosldrillingmarket@cosl.com.cn Accosl.com.cn
General Description	
Design/Generation	KFELS - B Class
Constructing Shipyard	KFELS shipyard PTE Ltd, Singapore
Year Enter Service/Significant Upgrades	2008
Classification	ABS
Flag	Bahamas
Displacement	15,480tons
Variable Deck	3,750tons
Operating Water Depth	400ft
Maximum Drilling Depth	30,000ft
Accomodation	112
Drilling Equipment	
Top Drive	NOV Varco TDS-8SA, 1150HP, 7,500psi
Draw works	NOV ADS-10T with3 x 1150HPAC
Derrick	Woolslayer Bolted H-beam
Cantilever	70ftx 15ft
Mud Pumps	LEWCO W-2215 x 3, 2 x 1,100HP each ,7,500 psi
Storage Capacities	
Fuel Oil	2,630bbls
Liquid Mud	3,613bbls
Base Oil	662bbls
Brine	1,939bbls
Drill Water	19,921bbls
Portable Water	2,053bbls
BOP & Subsea Equipment	
BOP Rams	Shaffer x 183/4"x15,000psi WP Dual Ram BOPs x2

These specifications are intended for general reference purposes only. All equipment shall be operated and maintained at all times, in compliance with COSL DRILLING standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.



BOP Annular	Shaffer X183/4"x10,000psiWP Annular
Diverter	Vetco Gray / KFDJ-2000
Other Information	
Cranes	50 ton x 3 + 12 ton x 1
Heli-deck	Sikorski S61 N Helicopter
Containment System	zero discharge





