

COSL PROSPECTOR



For Additional Information Please Contact:
COSL DRILLING
 Marketing Department
 P. O. Box 232, Beijing 101149, China, P.R.C
 Phone: +86 010 84522511
 Fax: +86 010 84522867
sh_cosldrillingmarket@cosl.com.cn
www.cosl.com.cn

General Description

Design/Generation	GG 5000
Constructing Shipyard	Yantai Raffles, China
Year Enter Service/Significant Upgrades	2014
Classification	DNV&CCS
Flag	Singapore
Displacement	40,849tons
Variable Deck	5,000tons
Operating Water Depth	4,500ft
Maximum Drilling Depth	22,250ft
Accommodation	130

Drilling Equipment

Top Drive	NOV HPS-03-750 2 AC KT
Draw works	NOV AHD 750-5750, 5,750hp continuous input power,2in drilling line
Derrick	NOV
Mud Pumps	3 x NOV Hex240 ,working pressure: 7,500 psi

Storage Capacities

Fuel Oil	20,127bbls
Liquid Mud	4,717 bbls (Active liquid mud) +6762bbls(Reserve liquid mud (column))
Base Oil	6,604bbls
Brine	10435bbls
Drill Water	8025 bbls
Portable Water	5,031bbls

BOP & Subsea Equipment

BOP Rams	2 x Shaffer 18 3/4in 15,000psi double rams; 3 x Shaffer 18 3/4in 15,000psi triple rams
----------	---

BOP Annular	Shaffer 18¾” 10000psi SFX Square shoulder (LMRP)
Moon Pool	72.6ft x 21ft
Tensioner	NOV / riser tensioner
Other Information	
Cranes	80t x 2
Heli-deck	Sikorsky S-92 / Super - Puma Helicopter
Station Keeping	DP3, POSMORATA

COSL PROSPECTOR



