

BO HAI 4 HAO



For the additional information please contact: MarketingDepartmentOf COSL Drilling

Telephone: +86 -10 -8452 2511

Email:sh_cosldrillingmarket@cosl.com.cn

Website: www.cosl.com.cn

Office address:

No.201, Haiyou Street, Yanjiao Developing Zone, Sanhe City, Hebei Province (Post Code: 065201)



General Description		
Design/Generation	Robray 300	
Constructing ShipyardHitachi Sh	nipbuilding & Engineering Co. Ltd	
Deliver Year/Upgrades	1977	
Classification	CCS	
Flag	China	
Overall Dimensions	287.91ft L \times 212ft W \times 27ft D	
Legs	417.33ft(127.2m)	
Usable leg below hull	350ft(106.6m)	
Spud-can diameter	54ft (16.5m)	
Draft at loadline	15ft (4.57m)	
Displacement	9578tons (2111.59kips)	
Drilling Variable Load	2455.83tons (5414.09kips)	
Cantilever Envelope	45ft $ imes$ \pm 12ft	
Operating Water Depth	91.44m(300ft)	
Max. Rating Drilling Depth	20,000ft(6096m)	
Accommodation	120 beds	

Drilling Equipment		
Derrick	Woolslayer Company, 160 ft. high, with 30ft. long $ imes$	
	30ft. wide base.	
Hookload Capacity	589 ton(1300 kips)	
Drawworks	National 1320 UDBE/G.E.752R1A 2×800 hp	
Top Drive	Varco / TDS-8SA, 1,150hp,	
	Test7,500psi/Working5,000psi	
Rotary Table	National /C-375	
Mud Pumps	Baoji Oil machinery Company / F-1600*2, TSC NF-	
	1600*1, working5,000psi / test 7,500psi	
Solid Control	4×NOV BRANDT/VSM 300	
Drilling Manifold	Rated for 5,000 Psi	

Drilling Manifold	Rated for 5,000 Psi
	Power Plant
Main Power	$4 \times$ Caterpillar 3516DITA diesel engines rated at
	1,609hp, 1,200 rpm
Emergency Power	$1 \times$ Caterpillar 3412DITA, 620Kw(831BHP)

STORAGE CAPACITIES		
Fuel Oil	515 m3 (18197.88ft3/3239bbl)	
Liquid Mud	338.35m3(2128 bbl)	
Brine	N/A	
Base Oil		
N/A		
Drill Water	861.3 m3(30415.1 ft3/5417bbl	
Potable Water	377.1 m3(13317.3 ft3/2372bbl	
Bentonite/barite	167.6	
m3(5922.54ft3/105	54bbl)	
Cement	167.6 m3(5922.54ft3/1054bbl)	
Sack Storage	4,000 sacks	
	BOP Equipment	
Diverter	N/A	
BOP annular	SHAFFER/13-5/8"/5000psi	
BOP rams	SHAFFER / TYPE U, 13-5/8"×10k Psi, Single Ram;	
	SHAFFER / TYPE U, 13-5/8"×10k Psi, Dual Ram;	
BOP handling	2×30 Tons, LETOURNEAU INC;	
	Cranes	
Port&Stbd	2×Amclyde Unit Lucker Division/ Unit -	
. Creases	10000HD/26.31tons/12.19m	
Port AFT	1×Amclyde Unit Lucker Division/Unit -	
· VICAII	10000HD/26.31tons/12.19m	
Knuckle-Boom	N/A	
	.,,,,	
	Mooring Equipment	
Mooring Winches	4× Marathon Letourneav co./ W-1500-TS,electic,.	
Anchor Lines	4×3280ft	
Anchors	4×Jiangsu yangyuan ship equipment Co.,	
	Ltd/Danforth 4540kg	
	OTHER FEATURES	
	OTHER FEATURES	
Helideck	Rated for Sikorsky S-61 helicopter	

These specifications are intended for general reference purposes only. All equipment shall be operated and maintained at all times, in compliance with COSL DRILLING standard operating manuals, policies and procedures, and within its stated operational limits or continuous rated capacity, in order to assure maximum operational efficiency.

Tension System





